

COMO

LOW VOC TYPE II

PHYSICAL PROPERTIES:

51" (130 CM) Vinyl Wallcovering, Type II

Total Weight: 20 oz./lin. yard (619 G/PLM)

13.3 oz./sq. yard (450 G/PSM)

Backing: Non-Woven

All patterns are stocked in 38 linear yard bolts and must be ordered in 19 yard increments.

FIRE HAZARD CLASSIFICATION RESULTS:

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 25

Smoke Development 35

Additional information is available at www.denovowall.com

All installations must conform to DeNovo's current Hanging Instructions and Product Technical information.

ANTI-MICROBIAL FEATURES:

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

BREATHE FREE™ MICRO-VENTING AVAILABLE UPON REQUEST:

Breathe Free™ Micro-vented wallcovering from DeNovo Wall can be used to help control un-wanted moisture inside a building envelope.

LIMITED WARRANTY:

3 year warranty against manufacturing defects. Additional information is available at www.denovowall.com

de
nōvō[®] WALL

Tel: 501-372-3550 Fax: 501-372-3553
www.denovowall.com
Made in the Netherlands

INSTALLATION NOTE

COMO is a random match / reversible pattern

For specifications and hanging instructions go to: www.denovowall.com

Copyright© 2016. All Rights Reserved
Any copying or other use is expressly prohibited
DeNovo Wall is a trademark.