

PHYSICAL PROPERTIES:

52"/54" (132/137 CM) Vinyl Wallcovering, Type II
 Total Weight: 20 oz./lin.yard (619 G/PLM)
 13.3 oz./sq.yard (451 G/PSM)
 Backing: Osnaburg



Mixed Sources
 Product group from well-managed
 forests and other controlled sources
 www.fsc.org Cert no. SGS-COC-004621
 © 1996 Forest Stewardship Council

Printed on FSC certified paper

FEDERAL SPECIFICATIONS:

KAYLA™ as manufactured by DeNovo Wall meets or exceeds G.S.A. Federal Specification CCC-W-408A through D for Type II materials using test procedures detailed in Federal Specifications CCC-T-191-B. This product has been accepted for use by the City of New York Department of Building. This wallcovering passes The National Fire Protection Association NFPA286 Corner Burn Test.

In addition, this product meets Type II CCC-W-408A through D requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance.

FIRE HAZARD CLASSIFICATION RESULTS:

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 15

Smoke Developed 25

Flame Spread
Class 1

Fire Propagation
Class 0

INSTALLATION REQUIREMENTS:

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

All installations must conform to Denovo's current Hanging Instructions and Product Technical information.

ANTI - MICROBIAL FEATURES:

Vinyl wallcoverings contain bactericides and mildew inhibitors to discourage the growth of mold and mildew under normal condition.

LIMITED WARRANTY:

For a period of five years from the date of shipment, we warrant that the product will conform to the published specifications and will be free from manufacturing defects when properly installed. **WE MAKE NO OTHER WARRANTY INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If the product fails to conform to this warranty, the customer's exclusive remedy is replacement or refund of the purchase price, at our sole option. We are not responsible for any incidental or consequential damages. This warranty gives you specific legal rights, and you may also have other legal rights which vary from state to state.

ENVIRONMENTAL STATEMENT:

We are dedicated to complying with today's environmental requirements, and have eliminated all heavy metals such as lead, mercury, cadmium and chromium from our inks and adhesives.

NOTE: The assigned numerical rating and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire conditions.

All patterns are stocked in 30 linear yard bolts and must be ordered in 15 yard increments.

INSTALLATION NOTE

KAYLA™ is a reversible match pattern.
 For hanging instructions go to: www.denovowall.com