

# MADRAS

# LOW VOC TYPE II

## PHYSICAL PROPERTIES:

51" (130 CM) Vinyl Wallcovering, Type II

Total Weight: 20 oz./lin. yard (619 G/PLM)

13.3 oz./sq. yard (450 G/PSM)

Backing: Non-Woven

All patterns are stocked in 38 linear yard bolts. Full bolts only.

---

## FIRE HAZARD CLASSIFICATION RESULTS:

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 25

Smoke Development 35

Additional information is available at [www.denovowall.com](http://www.denovowall.com)

All installations must conform to DeNovo's current Hanging Instructions and Product Technical information.

## ANTI-MICROBIAL FEATURES:

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

## BREATHE FREE™ MICRO-VENTING AVAILABLE UPON REQUEST:

Breathe Free™ Micro-vented wallcovering from DeNovo Wall can be used to help control un-wanted moisture inside a building envelope.

## LIMITED WARRANTY:

3 year warranty against manufacturing defects. Additional information is available at [www.denovowall.com](http://www.denovowall.com)



Tel: 501-372-3550 Fax: 501-372-3553  
[www.denovowall.com](http://www.denovowall.com)  
Made in the Netherlands

## INSTALLATION NOTE

MADRAS is a random match / reversible pattern

For specifications and hanging instructions go to: [www.denovowall.com](http://www.denovowall.com)

Copyright© 2016. All Rights Reserved  
Any copying or other use is expressly prohibited  
DeNovo Wall is a trademark.