

Block 35™

de novo® WALL

Type II

Physical Properties:	Total Weight	U.S. Units	Metric Units
		20 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	Fabric Type	Non-Woven	
	Material Width	52/54"	132/137 cm

**Federal Specifications:** Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

**Fire Hazard Classification Results:** **ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 15  
Passes NFPA 286 Corner Burn Test

**Performance Features:**

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

**Environmental Attributes:**

- Ultra-low emitting – Pass rating under CA 01350
- NSF/ANSI 342 certified for sustainability

**Permeability, Moisture and Mold:** Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.  
Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

**INSTALLATION NOTE**

**Block 35™** is a reversible match pattern

For specifications and hanging instructions go to: [www.denovowall.com](http://www.denovowall.com)

de novo® WALL

Tel: 501-372-3550 Fax: 501-372-3553  
[www.denovowall.com](http://www.denovowall.com)

Copyright© 2018. All Rights Reserved  
Any copying or other use is expressly prohibited  
DeNovo Wall is a trademark.

MADE IN USA

